

## DIGITAL DIMMER

# ELECON



Four seasons Hotel, Bangkok

# Lighting Control System

Products can be made to order asper requirements.



### Spec Function

- 1 เป็นระบบ DIGITAL DIMMER ควบคุมการทำงานด้วยไมโครโปรเชสเซอร์มีความละเอียดในการ dim 256 step จาก 0–100 %
- 2 มีระบบป้องกันการ short circuit และ over load ด้วย MINIATURE CIRCUIT BREAKER
- 3 มีระบบระบายความร้อนด้วย heat sink และพัดลมอากาศ
- 4 มีการแยกวงจร Control ออกจากภาค Power ดวย Opto Isolator (Isolation Voltage>7,500)
- 5 สามารถควบคุม load ใต้ถึง 12 channel x 5000 w
- 6 สามารถใช้กับหลอด (หลอดใส้) Incandescent, Halogen lowvoltage, Tungsten, Fluorscent
- 7 ใช้ใต้กับไฟ 1 Phase 2 Wires 220 VAC . 50 Hz หรือ Phases 3 Wires 220/380 VAC . 50 Hz
- 8 สามารถเลือก dim up/down on/off แต่ละ channel ใค้อิสระ
- 9 สามารถตั้งโปรแกรม Scene ได้สูงสุด 12 โปรแกรม
- 10 สามารถตั้งโปรแกรม Fadetime ให้ตั้งแต่ 0-90 วินาที อิสระแต่ละ Scene
- 11 สามารถบยาย Channel dimmer ใก้ด้วยการต่อแบบ Master/Slave โดยบยายใก้สูงสุด 20 rack (120 channel)
- 12 สามารถต่อ Remote ใก้สูงสุด 4 จุด
- 13 สามารถเพิ่มหรือลดความสว่างแบบ Group
- \* สำหรับ Load Fluorescent เป็น option

#### FUNCTION DIAGRAM (7 CHANNEL) RE SE TE N จอ DISPLAY LED แสดงสถานะ ปุ่ม CH.ON/OFF 12:00 CH1 CH2 CH3 CH4 ปุ่ม MASTER ON/OFF SCENE SCENE SCENE MAKING พร้อม LED แสดงสถานะ SCHE SCHE SCHE SCHE U ปุ่ม CH.DOWN ปุ่ม CH.UP DIMMER ปุ่มเลือก mode พร้อม led แสดง สถานะ ปุ่มเลือก scene พร้อม led แสดง สถานะ REMOTE

## FEATURES AND FUNCTION



Support a maximam of 10,000-watt dimmer capacity with 8 channel, each channel supplying a maximum of 3000 watt

Adjustable up to 256 steps from 0-90% Adjustable up to 10 steps of fade time with 4 channels.

## DIMMER MODEL






Holiday Inn Hotel











5 Channel X 2 KW and MASTER

DIMMER PANEL

#### Energy Savings

Dimming lighting saves energy. Elecon digital dimmer creates an energy efficient environment, with up to 98 % of the corresponding unused lighting energy saved through dimming, and bulb life prolonged by 30 % or more because fading a lamp digitally is gentle on the filament than just switching it on or off.



#### Software dimmer

Programming / Operating Software Runs using an RS485 Interface. Any circuit can be set as any physical channel and programmed to be on any phase, in any zone or set as a switch or dimming channel. For each scene, the circuits can be programmed, temporarily re-adjusted, modified, set for on/off switching



# SOFTWARE

Hall, The Sukhothai Hotel



Soft-touch button for comfort

ELECON



## Elecon Digital Dimmer Features

#### Digital Dimming Controlled by Updeated Microprocessor

3 phase or single Phase dimming or Switching

Independent Dim or Non-Dim Function

Variable Fade Rates from 0.5 Seconds (to gradually turn lights on/off)

3 Data Buses Including

• RS 485

• RS 232

Remote Control

Internal Programming by LED Control Panel

24-Hr 7-Day Built-in Event timer (Battery backed)

Main voltage compensation and voltage stabilization

Filament Preheat can be selected on a per channel basis

Operation setting from internal or Frontal control panel

Compatible with incandescent, Halogen, High pressure sodium, Mercury and Fluorescent

LED indicator display of load system on a per channel

Solid state thyristor phase power control system (SCR back to back)

Programming and operation from:

- LED control panel
- Remote control

Automatic switch to set master for manage system control

LED indicator display of load system on a per channel

Voltage isolation between the control system and power system is ensured safety by the opto-isolator

RFI suppression noise protection system employing thr toroid choke and R-C network

System is protecte from excess power or short circuiting by maniature circuit breaker

45'c maximum ambient temperature for 100% duty cycle

## **TYPE: DIMMER**






BANYAN TREE, Bangkok

Holoday Inn Resort, Phoket

LIGHT



BRIGTH



**SMOOTH** 



ATMOSPHERE COMFORTABLE

## Light & Smooth

# ELEGON

SCENE CH.2

SCENE CH.3

SCENE CH.4

SCENE CH.4



Scene Panel

## Digital Dimmer is designed to control dimmer for:

- Hotel & Commercials
- Spa
- Convention Center
- Cinemas
- Broadcast studios

- Residentials
- Restaurants
- Conferences
- Entertainments
- Cruise ships

## Technical Specification

Electronic phase Control Dimmer

Channel 2 / 4 / 6 / 8 Channel

Power Input 1 Phase 2 Wires 220 VAC.50 Hz

3 Phase 4 Wires 220/380 VAC.50/60 Hz

Load Output 1 KW 2 KW 5 KW 10 kw

Input Control Digital: RS-485 or dmx-512

Analog: 0-10 VDC.

Scene: Program by microprocessor

scene panel

Display Led 7 - Seqment, 4 Digit

Over heat protection Step 1 : Fan on

Step 2 : Dim down automatic

Step 3: All dimmer off

Short circuit protection By Mcb

Surge protection


Type of dimmer


Ambient Temperature | 45

45'c maximum, generously rated

heatsinks limit internal temperature

Four seasons Hotel, Bangkok





ELEGON

Compatible with incandescent,
Halogen, High pressure sodium,
Mercury and Fluorescent



Electronic Ballast



Low voltage halogen lamp



Incandescent



Fluorescent



#### Soft-touch control

## **Digital Dimmer**

access: 22 http://:www.elecon.co.th



Digital and micro-controller-based, ELECON
Digital Dimmer promises to bring forth comfort,
ease and style to your guests by just
on click of a button.

+From the latest of technologies comes the state-of-the-art



Best for hotel, resorts, restaurants and even right in the heart of your own homes.





+Soft-touch button for comfort, Ease and Style







#### Design and manufactured by :

ELECON INTERNATIONAL CO.,LTD 122 Soi Intraporn Wangthonglang,Wangthonglang, Bangkok 10310 Thailand

Tel. (66) 2933-5991-5 Fax. (66) 2933-5990 E-mail: elecon@ksc.th.com www.elecon.co.th

#### Distributed by:

METRO LIGHT & SOUND
ENTERPRISE
No. 43 Jalan Kasawari 9 B,
Bandar Puchong Jaya,
47100 Puchong Selangor D.E.
Tel. 03-8 8312
Unitech Industrie
15 west Coast Hig
pasir Panjang Bui
Tel. (65) 6778 5885
Tel. 03-8 8312

#### Distributed by:

Unitech Industries Pte.,Ltd 15 west Coast Highway #04-03 pasir Panjang Buiding singapore 117861 Tel. (65) 6778 5885 Fax. (65) 6778 8885